

CB3000 Client Bridge

Wireless LAN Interface for Ethernet Devices

CLIENT BRIDGES AND ADAPTERS

Simple, cost-effective high performance wireless connectivity for printers, point-of-sale and Ethernet enabled devices

The CB3000 provides a robust wireless connection for your Ethernet-enabled devices — from printers, scales, medical equipment, and manufacturing machinery to time clocks, point-of-sale devices and more. The need to extend wiring is eliminated, reducing the cost and complexity of deployment for devices without a PCMCIA or PCI card slot. And the ability to update the firmware provides the investment protection you need, ensuring that the CB3000 meets your networking needs today as well as tomorrow.

Increase productivity throughout your enterprise

The CB3000 allows you to cost-effectively extend the availability of applications, devices, and real-time data, resulting in a productivity increase throughout your enterprise. The ability to move information from time clocks directly into your payroll application eliminates time spent manually processing time cards. The ability to collect statistics from manufacturing machinery enables early identification and resolution of equipment problems — before they impact yield. And the wireless connection enables network changes to be executed quickly and easily, as needed — for example, to connect point-of-sale devices to support a sale in a specific area of the store.

Easy to deploy and manage with enterprise functionality

The CB3000 offers the simplicity of true plug-and-play deployment — minimal configuration is required. Your wireless client devices enjoy uninterrupted connectivity — the CB3000 can easily roam to another access port or access point as needed. And a secure internal web server provides the convenience of anywhere anytime management through any standard web browser.

A secure, reliable, easy to move connection

The CB3000 provides the enterprise-class security you need — advanced encryption and authentication mechanisms protect your network and data from unauthorized users. And wireless connectivity offers maximum flexibility. Equipment can be easily moved as needed to accommodate seasonal requirements as well as line and staffing changes, without the time and expense of re-wiring.



FEATURES

BENEFITS

IEEE 802.11a/b/g

Flexibility to connect to multiple network technologies

Multi-client support

Affordable connectivity for up to 16 client devices

IBM POS protocol support

Cost-effective wireless deployment for point-of-sale devices

WEP 40/128, WPA and AES encryption; 802.1x support with PEAP, EAP/TLS, EAP/TTLS authentication

Provides rigorous security for your data and network

Embedded secure web server

Convenient anytime anywhere management

SNMP v2 support

Integrates easily with standard enterprise management systems

Ad hoc mode (CB3000 to CB3000 – networking of all connected devices)

Quickly and inexpensively enable the sharing of printers and other peripherals, server access and more

Connect up to 16 devices in nearly any environment

The robust mechanical design and support for a wide range of temperatures delivers reliable performance throughout your enterprise, from your front office to the retail, warehouse or factory floor. And when used in conjunction with an Ethernet hub, a single CB3000 can connect up to 16 client devices to your Symbol wireless switches, access ports and access points, making the CB3000 an outstanding value.

An ideal companion for your mobility solution

The CB3000 – a flexible and very economical wireless connection enabling the movement of data to and from many types of devices, with the reliability, performance and security you expect in Symbol enterprise mobility solutions. Symbol Services also offers the comprehensive support and technical expertise you need to design, deploy and maintain the most successful mobility solutions.

For more information on the CB3000, contact us at +1.800.722.6234 or +1.631.738.2400, or visit us on the Web at

www.symbol.com/wireless/cb3000

CB3000 Specifications

Physical Characteristics

Dimensions:	7.0 in. L x 4.0 in. W x 1.2 in. D/179 mm L x 102 mm W x 31 mm D
Interfaces:	Ethernet Interface: RJ-45 10/100Base-T; 802.11a/b/g
LEDs:	Power (Status/Error), WLAN (802.11a/802.11g), LAN (10/100 Mb)
Operating Temp:	32° to 122° F/0° to 50° C
Humidity:	10% – 90% non-condensing

Software Specifications

Security:	WPA2/802.11i; 802.1x Supplicant, PEAP, EAP/TLS, EAP/TTLS
Network Protocol Support:	TCP/IP, DHCP, SNMP v2

Network Management:	Embedded Secure Web server; SNMP v2 support, Discovery Tool included for all bridges in Layer 2 network																																																																								
POS Protocol Support:	RPL, PXE; Limit one RPL or PXE terminal per bridge																																																																								
Standards:	IEEE 802.11a/b/g; IEEE 802.3; IEEE 802.1d; 802.11i; 802.11h (DFS/TCP); HTTPS																																																																								
Compatibility																																																																									
Supported Devices:	Windows-based PCs equipped with Ethernet cards; point-of-sale devices; network printers; thin clients; Mac/Apple machines; Linux/ Unix workstations; Ethernet-enabled appliances; and/or mix of all devices listed																																																																								
Device Manager:	Windows 2000, Windows XP																																																																								
Radio Characteristics																																																																									
Frequency Range:	802.11a: 5.150—5.825 GHz 802.11b/g: 2.4—2.4835 GHz																																																																								
Data Rate:	802.11a/g: 54, 48, 35, 24, 18, 12, 9 & 6 Mbps 802.11b: 11, 5.5, 2 & 1 Mbps																																																																								
Radio Sensitivity (minimum):	<table border="0"> <tr> <td>802.11b</td> <td>1 Mbps</td> <td>-97 dBm</td> <td>802.11g</td> <td>6 Mbps</td> <td>-91 dBm</td> </tr> <tr> <td></td> <td>2 Mbps</td> <td>-93 dBm</td> <td></td> <td>9 Mbps</td> <td>-89 dBm</td> </tr> <tr> <td></td> <td>5.5 Mbps</td> <td>-91 dBm</td> <td></td> <td>12 Mbps</td> <td>-89 dBm</td> </tr> <tr> <td></td> <td>11 Mbps</td> <td>-85 dBm</td> <td></td> <td>18 Mbps</td> <td>-85 dBm</td> </tr> <tr> <td>802.11a</td> <td>6 Mbps</td> <td>-90 dBm</td> <td></td> <td>24 Mbps</td> <td>-84 dBm</td> </tr> <tr> <td></td> <td>9 Mbps</td> <td>-88 dBm</td> <td></td> <td>36 Mbps</td> <td>-80 dBm</td> </tr> <tr> <td></td> <td>12 Mbps</td> <td>-87 dBm</td> <td></td> <td>48 Mbps</td> <td>-76 dBm</td> </tr> <tr> <td></td> <td>18 Mbps</td> <td>-85 dBm</td> <td></td> <td>54 Mbps</td> <td>-74 dBm</td> </tr> <tr> <td></td> <td>24 Mbps</td> <td>-81 dBm</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>36 Mbps</td> <td>-79 dBm</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>48 Mbps</td> <td>-73 dBm</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>54 Mbps</td> <td>-72 dBm</td> <td></td> <td></td> <td></td> </tr> </table>	802.11b	1 Mbps	-97 dBm	802.11g	6 Mbps	-91 dBm		2 Mbps	-93 dBm		9 Mbps	-89 dBm		5.5 Mbps	-91 dBm		12 Mbps	-89 dBm		11 Mbps	-85 dBm		18 Mbps	-85 dBm	802.11a	6 Mbps	-90 dBm		24 Mbps	-84 dBm		9 Mbps	-88 dBm		36 Mbps	-80 dBm		12 Mbps	-87 dBm		48 Mbps	-76 dBm		18 Mbps	-85 dBm		54 Mbps	-74 dBm		24 Mbps	-81 dBm					36 Mbps	-79 dBm					48 Mbps	-73 dBm					54 Mbps	-72 dBm			
802.11b	1 Mbps	-97 dBm	802.11g	6 Mbps	-91 dBm																																																																				
	2 Mbps	-93 dBm		9 Mbps	-89 dBm																																																																				
	5.5 Mbps	-91 dBm		12 Mbps	-89 dBm																																																																				
	11 Mbps	-85 dBm		18 Mbps	-85 dBm																																																																				
802.11a	6 Mbps	-90 dBm		24 Mbps	-84 dBm																																																																				
	9 Mbps	-88 dBm		36 Mbps	-80 dBm																																																																				
	12 Mbps	-87 dBm		48 Mbps	-76 dBm																																																																				
	18 Mbps	-85 dBm		54 Mbps	-74 dBm																																																																				
	24 Mbps	-81 dBm																																																																							
	36 Mbps	-79 dBm																																																																							
	48 Mbps	-73 dBm																																																																							
	54 Mbps	-72 dBm																																																																							
Nominal Transmitter Power:	<table border="0"> <tr> <td>802.11b/g</td> <td>20.5 dBm +1/-1.5 dBm @ 1, 2, 5.5, 11 Mbps</td> </tr> <tr> <td></td> <td>20.5 dBm +1/-1.5 dBm @ 6, 9, 12, 18, 24 Mbps</td> </tr> <tr> <td></td> <td>18.5 dBm +1/-1.5 dBm @ 36 Mbps</td> </tr> <tr> <td></td> <td>17.5 dBm +1/-1.5 dBm @ 48 Mbps</td> </tr> <tr> <td></td> <td>16.5 dBm +1/-1.5 dBm @ 54 Mbps</td> </tr> <tr> <td>802.11a</td> <td>20.5 dBm +1/-1.5 dBm @ 6, 9, 12, 18, 24 Mbps</td> </tr> <tr> <td></td> <td>16.5 dBm +1/-1.5 dBm @ 36 Mbps</td> </tr> <tr> <td></td> <td>15.5 dBm +1/-1.5 dBm @ 48 Mbps</td> </tr> <tr> <td></td> <td>14.5 dBm +1/-1.5 dBm @ 54 Mbps</td> </tr> </table>	802.11b/g	20.5 dBm +1/-1.5 dBm @ 1, 2, 5.5, 11 Mbps		20.5 dBm +1/-1.5 dBm @ 6, 9, 12, 18, 24 Mbps		18.5 dBm +1/-1.5 dBm @ 36 Mbps		17.5 dBm +1/-1.5 dBm @ 48 Mbps		16.5 dBm +1/-1.5 dBm @ 54 Mbps	802.11a	20.5 dBm +1/-1.5 dBm @ 6, 9, 12, 18, 24 Mbps		16.5 dBm +1/-1.5 dBm @ 36 Mbps		15.5 dBm +1/-1.5 dBm @ 48 Mbps		14.5 dBm +1/-1.5 dBm @ 54 Mbps																																																						
802.11b/g	20.5 dBm +1/-1.5 dBm @ 1, 2, 5.5, 11 Mbps																																																																								
	20.5 dBm +1/-1.5 dBm @ 6, 9, 12, 18, 24 Mbps																																																																								
	18.5 dBm +1/-1.5 dBm @ 36 Mbps																																																																								
	17.5 dBm +1/-1.5 dBm @ 48 Mbps																																																																								
	16.5 dBm +1/-1.5 dBm @ 54 Mbps																																																																								
802.11a	20.5 dBm +1/-1.5 dBm @ 6, 9, 12, 18, 24 Mbps																																																																								
	16.5 dBm +1/-1.5 dBm @ 36 Mbps																																																																								
	15.5 dBm +1/-1.5 dBm @ 48 Mbps																																																																								
	14.5 dBm +1/-1.5 dBm @ 54 Mbps																																																																								
Modulation:	DSSS (Direct Sequence Spread Spectrum), OFDM (Orthogonal Frequency Division Multiplexing)																																																																								
Range:	Up to 1,000 ft./300 m in open environment (range varies based on environment)																																																																								
Regulatory																																																																									
Electrical and Mechanical Safety:	cUL1950; EN60950 and IEC60950																																																																								
EMC:	FCC Part 15B; ICES-003 Class B; EU EN 301 489 Parts 1 & 17; EN 60601-1-2 (Medical)																																																																								
Radio:	FCC Part 15.247, 15.205, 15.209, 15.207, 15.203, 15.407; Canada: RSS-210; EU EN 300 328 (2.4GHz), EN 301 893 (5GHz); Japan ARIB STD-66, 33 & 771																																																																								

About Symbol Technologies

Symbol Technologies, Inc., The Enterprise Mobility Company™, is a recognized worldwide leader in enterprise mobility, delivering products and solutions that capture, move and manage information in real time to and from the point of business activity. Symbol enterprise mobility solutions integrate advanced data capture products, radio frequency identification technology, mobile computing platforms, wireless infrastructure, mobility software and world-class services programs under the Symbol Enterprise Mobility Services brand. Symbol enterprise mobility products and solutions are proven to increase workforce productivity, reduce operating costs, drive operational efficiencies and realize competitive advantages for the world's leading companies. More information is available at www.symbol.com



Corporate Headquarters
Symbol Technologies, Inc.
 One Symbol Plaza
 Holtville, NY 11742-1300
 TEL: +1.800.722.6234
 +1.631.738.2400
 FAX: +1.631.738.5990

For Asia Pacific Area
Symbol Technologies Asia, Inc.
 (Singapore Branch)
 Asia Pacific Division
 230 Victoria Street #05-07/09
 Bugis Junction Office Tower
 Singapore 188024
 TEL: +65.6796.9600
 FAX: +65.6337.6488

For Europe, Middle East and Africa
Symbol Technologies
 EMEA Division
 Symbol Place, Winnersh Triangle
 Berkshire, England RG41 5TP
 TEL: +44.118.9457000
 FAX: +44.118.9457500

For North America, Latin America and Canada
Symbol Technologies
 The Americas
 One Symbol Plaza
 Holtville, NY 11742-1300
 TEL: +1.800.722.6234
 +1.631.738.2400
 FAX: +1.631.738.5990

Symbol Website
 For a complete list of Symbol subsidiaries and business partners worldwide contact us at:
www.symbol.com
E-mail
info@symbol.com



DS-CB3000 06/05

Part No. DS-CB3000 Printed in USA 06/05 © Copyright 2005 Symbol Technologies, Inc. All rights reserved. Symbol is an ISO 9001 and ISO 9002 UKAS, RVC, and RAB Registered company, as scope definitions apply. Specifications are subject to change without notice. Symbol® is a registered trademark of Symbol Technologies, Inc. All other trademarks and service marks are proprietary to their respective owners. For system, product or services availability and specific information within your country, please contact your local Symbol Technologies office or Business Partner.